



CAB4/2C/AB 4 Core Alarm Cable Carton ADI Benelux

200mtr

Construction

Group	Signal Cores	Power Cores
Conductor		
Material	Tinned annealed stranded Cu	n/a
Nominal Diameter	Ø 0.546mm = 7xØ 0.182	n/a
Area	0.182mm ²	n/a
Insulation		
Material	Type 2, Type TI 1PVC	n/a
Nominal Diameter	Ø 1.0mm	n/a
Min wall	0.2mm	n/a
Colours	see colour table	n/a
Mylar Layer		
Coverage	n/a	
Drain Wire		
Material	n/a	
Nominal Diameter	n/a	
Area	n/a	
Screen		
Material	n/a	
Coverage	n/a	
Rip cord	Polyester 1100 Desitex 40 Nm breaking strain.	
Sheath		
Material	Tubed PVC Type 6, Type TM 1	
Colour	White	
Nominal Diameter	Ø 3.4mm	
Min wall	Ø 0.4mm	
Sheath Marking		
Printing	n/a	
Color	n/a	
Frequency	n/a	

Packaging


Box	308mmx290mmx85 mm	Box A / Printed CQR
-----	-------------------	---------------------

Labelling

Barcode	5060399120043 Yellow
Artwork No:	6405

Gross Weight (nominal)

3.695Kgs

 <p>Not to scale</p>	<p>Issue 02 Date 03/07/2014 CRJ</p>	<p>CQR Security Tarran Way Ind Est Moreton Wirral CH46 4TH www.cqr.co.uk</p>
---	---	--

Electrical characteristics

Group	Signal Cores	Power Cores
Max conductor DC Nominal resistance	94.6 Ω /Km	n/a
Rated Voltage	50V	n/a
Insulation resistance @20°C	\approx 200 M Ω /Km	n/a

Thermal Characteristics

Rated Temperature	-10°C to +70°C
-------------------	----------------

Colour Table

Signal	Power	Status
	Red	✗
	Black	✗
White		✓
Red		✓
Yellow		✓
Green		✓
Grey		✗
Orange		✗
Turquoise		✗
Brown		✗
Violet		✗
Black		✗
Blue		✗
Pink		✗
White / brown stripe		✗
White / violet stripe		✗
White / green stripe		✗
White / blue stripe		✗
White / grey stripe		✗
White / yellow stripe		✗
White / black stripe		✗
White / red stripe		✗

Customer

ADI Benelux

Standards

N/A
