



CAB6/5R/AB 6 Core Alarm Cable 500mtr reel ADI Benelux

Construction

Group	Signal Cores	Power Cores
Conductor		
Material	Tinned annealed stranded Cu	n/a
Nominal Diameter	Ø 0.546mm = 7xØ 0.182mm	n/a
Area	0.182mm ²	n/a
Insulation		
Material	PVC	n/a
Nominal Diameter	Ø 1.0mm	n/a
Min wall	0.2mm	n/a
Colours	see colour table	n/a
Mylar Layer		
Coverage	n/a	
Drain Wire		
Material	n/a	
Nominal Diameter	n/a	
Area	n/a	
Screen		
Material	n/a	
Coverage	n/a	
Rip cord	Polyester 1100 Desitex 40 Nm breaking strain.	
Sheath		
Material	PVC	
Colour	White	
Nominal Diameter	Ø 3.9mm	
Min wall	Ø 0.4mm	
Sheath Marking		
Printing	n/a	
	n/a	
Color	n/a	
Frequency	n/a	

Packaging


Reel	Constructed Reel	10½" Flange 3"x 6" Tin
------	------------------	------------------------

Labelling

Barcode	5060399120081 Pink
Artwork No:	6409

Gross Weight (nominal)

12.8 Kgs

<i>Not to scale</i> 	Issue 02 Date 03/07/2014 CRJ	CQR Security Tarran Way Ind Est Moreton Wirral CH46 4TH www.cqr.co.uk
----------------------------------------------------------------------------------------------------------	------------------------------------	----------------------------------------------------------------------------------------------------------------------

Electrical characteristics		
Group	Signal Cores	Power Cores
Max conductor DC Nominal resistance	94.6 Ω /Km	n/a
Rated Voltage	50V	n/a
Insulation resistance @20°C	\approx 200 M Ω /Km	n/a

Thermal Characteristics	
Rated Temperature	-10°C to +70°C

Colour Table		
Signal	Power	Status
	Red	✗
	Black	✗
White		✓
Red		✓
Yellow		✓
Green		✓
Grey		✓
Orange		✓
Turquoise		✗
Brown		✗
Violet		✗
Black		✗
Blue		✗
Pink		✗
White / brown stripe		✗
White / violet stripe		✗
White / green stripe		✗
White / blue stripe		✗
White / grey stripe		✗
White / yellow stripe		✗
White / black stripe		✗
White / red stripe		✗

Customer
ADI Benelux

Standards
N/A