
	CABTP3X2/1C/AB 6 Core Twisted Pairs 3 x 2 x 22 AWG Belden Type Low smoke and Fume White 100mtr
Construction	
Group	Each Signal Pair Twisted with drain and screened
Conductor	
Material	Tinned annealed stranded Cu
Nominal Diameter	$\varnothing .75\text{mm} = 7 \times \varnothing 0.25\text{mm}$
Area	0.344mm^2
Insulation	
Material	Low Smoke and Fume
Nominal Diameter	$\varnothing 1.2\text{mm}$
Min wall	0.3mm
Colours	Pairs are Black/ Red and Green/ White
Mylar Layer	
Coverage	25micron x 14mm width over each screen
Drain Wire	
Material	Tinned annealed (twisted) stranded Cu
Nominal Diameter	$\varnothing 0.57\text{mm} = 7 \times \varnothing 0.190\text{mm}$
Area	0.198mm^2
Screen	
Material	Alu/Polyester Foil 14mm width
Coverage	Minimum 10% overlap
Rip cord	N/A
Sheath	
Material	Low Smoke and Fume
Colour	White
Nominal Diameter	$\varnothing 6.75\text{mm}$
Min wall	$\varnothing 0.7\text{mm}$
Sheath Marking	
Printing	N/A
Color	
Frequency	
Packaging	
Box	Box B Red Printed CQR
Labelling	
Barcode	LABCABTP/3X2/1C/AB + 5060399120654
Artwork No:	6467
Gross Weight (nominal)	
5.4Kgs	

 <p>Not to scale</p>	<p>Issue 02 Date 03/07/2014 CRJ</p>	<p>CQR Security Tarran Way Ind Est Moreton Wirral CH46 4TH www.cqr.co.uk</p>
Group	Signal Cores	Power Cores
Max conductor DC Nominal resistance	50.1 Ω /Km	n/a
Rated Voltage	50V	n/a
Insulation resistance @20°C	\approx 200 M Ω /Km	n/a

Thermal Characteristics	
Rated Temperature	-10°C to +70°C

Colour Table		
Signal	Power	Status
	Red	✗
	Black	✗
White		✓
Red		✓
Yellow		✗
Green		✓
Grey		✗
Orange		✗
Turquoise		✗
Brown		✗
Violet		✗
Black x 3		✓
Blue		✗
Pink		✗
White / brown stripe		✗
White / violet stripe		✗
White / green stripe		✗
White / blue stripe		✗
White / grey stripe		✗
White / yellow stripe		✗
White / black stripe		✗
White / red stripe		✗

Customer
ADI Benelux

Standards
N/A