MC 346

Magnetic Contact,
Recessed mounting, NC/NO

Product :

Montage	Recessed mounting
Circuit du contact	Contact inverseur (NF/NO)
Certifications	EN 50131-2-6 Grade 2, Class IIIA, INCERT B-582-0014, SBSC 9-203, Class 1/2, NBU T02-3/2019, FG
Cote commutateur	48 VDC / 250 mA / 5 VA
Diamètre de perçage mm	8
Aimant (type)	Alnico 5
Installation sur bois	Non recommandé
Distance de fermeture (bois) mm	13
Distance de fermeture en mm (acier)	X
Autoprotection	Oui
Connexion	Câble (connection de cable perpendiculaire)
Matériau du coffret	ABS Plastic
Température de fonctionnement	-40°C – +70°C
Indice de protection	IP 67
Dimensions du commutateur (L x Ø) mm	36 x 9
Dimensions de l’aimant (L x Ø) mm	26 x 6
Grade	2

Product description:

MC 346 is a universal magnetic contact with change-over (NC/NO) function that can be used in both alarm and access control systems for monitoring e.g. doors and windows against unauthorized opening. Both the contact and the magnet part are in a water proof (IP 67) plastic housing, which enables easy installation into wood without additional accessories. With our extensive range of installation accessories it is easy to install the contact either recessed or as a surface mount.

Related products and accessories

	MC 300-S1 Plastic flanges for MC 340, 346, 347, 370
	**MC 300-S3** Plastic Housing for MC 340, 346, 347
	MC 300-S11 Plastic Flange for MC 340, 346, 347 and 370
	MC 300-S21 Plastic Snap-in Flange for MC 340, 346, 347, 370
	MC 300-S22 Snap-in Flange with Strong Magnet for MC 340, 346, 347

Related products and accessories

	MC 300-S31 Plastic Snap-in Flange for MC 340, 346, 347, 370
	MC 300-S32 Snap-in Flange with Strong Magnet for MC 340, 346, 347
	MC 300-S35 Plastic Housing for MC 340, 346, 347